Neptun



Charcteristics	Standard	Unit	Result
Type of flooring	ISO 10581 - EN 649		Vinyl Wall Covering
Material			Polyvinyl chloride
Cover			UV
Category			Compact
Safety criteria			
Flammability	EN 13501-1	class	B-s2,d0
Sound	ISO 10140	dB	2
Slip resistance	DIN 51130	group	R9
Dynamic coefficient of friction	EN 13893		≥0.3
Performance behaviour			
Sheet width	ISO 24341 - EN 426	m	2
Sheet length	ISO 24341 - EN 426	m	20
Overall thickness	ISO 243416 - EN 428	mm	1.2
Wear layer thickness	ISO 24340	mm	0.15
Total weight	ISO 23997 - EN 430	g/m²	2000
Wear resistance	EN 649	group	T
Residual indentation	ISO 24343 -1 - EN 433	mm	≤0.16
Dimensional stability	ISO 23999 - EN 434	%	0.05~0.10
Color fastness	ISO 105 - B02	rating	≥ 6
Resisitance to staining	EN 423		No stain
Bend resistance	GB/T 11982.2 - 2015		No
Antibacterial	ISO 22196		Level 1
Anti iodine			Good
Classification			
Domestic	ISO 10874 - EN 685	class	23 heavy duty
Commercial	ISO 10874 - EN 685	class	34 very heavy duty
Industrial	ISO 10874 - EN 685	class	43 heavy duty
Additional property			

Castor Chair	√	Antistatic Behavious	√
Underfloor Heating	√	Chemical Resistance	√

CE ISO 9001 SGS ISO 14001 SGS PHTHALATE FREE 100% RECYCLABLE Formaldehyde Free ECO FRIENDLY Better Indoor Air Quality

Wolflor® flooring expert

IAAN® we grow together